

# Treadmill Comparison

Display Console	TR500	TR1000	TR2000	TR3000	PRO 3	PRO 5
Display Panel	Oversized Blue Backlit Display with Program Matrix	Oversized Blue Backlit Display with Program Matrix	Two Color LCD Backlit Display with Program Matrix	Two Color LCD Backlit Display with Program Matrix	3 Red LED Displays 30 x 16 LCD Program Matrix	Multi-Colored Program Matrix 15 Character Alphanumeric LED 3 Single Panel LED Displays
Readouts	Incline, Speed, Time, Distance, Calories, Heart Rate	Incline, Speed, Time, Distance, Calories, Heart Rate	Incline, Speed, Time, Distance, Calories, Heart Rate, Step Count	Incline, Speed, Time, Distance, Calories, Heart Rate, Step Count	Heart Rate, Incline, Speed, Distance, Time, Calories, Lap Count	Heart Rate, Incline, Speed, Distance, Time, Calories, Lap Count
Heart Rate	Contact Heart Rate	Contact Heart Rate	Contact Heart Rate and Chest Strap Receiver (chest strap not included)	Contact Heart Rate and Chest Strap Receiver (chest strap not included)	Contact Heart Rate and Chest Strap Receiver	Contact Heart Rate and Chest Strap Receiver (chest strap not included)
Speed / Incline Control	Quick Speed & Incline Buttons Handlebar Speed & Incline Control	Quick Speed & Incline Buttons Handlebar Speed & Incline Control	Quick Speed & Incline Buttons Handlebar Speed & Incline Control	Quick Speed & Incline Buttons Handlebar Speed & Incline Control	Quick Speed & Incline Buttons Handlebar Speed & Incline Control	Quick Speed & Incline Buttons
<b>Mechanical Performance</b>						
Speed	.06 – 10 MPH	.06 – 10 MPH	.05 – 10 MPH	.05 – 12 MPH	.05 – 12 MPH	.05 – 12 MPH
Incline Levels	0 – 12 Levels	0 – 12 Levels	5 Decline / 10 Incline	0 – 15 Levels	0 – 15 Levels	0 – 15 Levels
Belt Size	18" x 52"	20" x 56"	20" x 56"	20" x 56"	22" x 60"	22" x 62"
Belt Type	2 Ply Anti-Static	2 Ply Anti-Static	2 Ply Anti-Static	2 Ply Anti-Static	Multi-Ply with 2 ply no - stretch and 2 ply PVC	Multi-Ply with 2 ply no - stretch and 2 ply PVC
Roller Size	2" Tapered	2.4" Tapered Front 2" Rear	2.5" Tapered	2.5" Tapered Front 2" Rear	3.0" Tapered Front 2.5" Rear	3.0" Tapered Front 3.0" Rear
Frame	Heavy Gauge Steel Welded Frame	Heavy Gauge Steel Welded Frame	Heavy Gauge Steel Welded Frame	Heavy Gauge Steel Welded Frame	Extra-Heavy Gauge Steel Welded Frame	Extra-Heavy Gauge Steel Welded Frame
Fold	Yes – EZ Drop	Yes – EZ Drop	Yes – EZ Drop	Yes – EZ Drop	No	No
Side Rails	Non-Slip Plastic	Non-Slip Plastic	Non-Slip Plastic	Aluminum	Aluminum (top) Extrusion	Aluminum (top & side) Extrusion
Deck	¾" with 8 Variable Density Elastomers	¾" with 8 Variable Density Elastomers	1" with 8 Variable Density Elastomers	1" with 8 Variable Density Elastomers	1" Reversible Density Elastomers	1" Reversible Density Elastomers
Drive Motor	1.75 HP Continuous Duty	2.0 HP Continuous Duty	2.5 HP Continuous Duty	2.75 HP Continuous Duty	3 HP - DC	3 HP - AC
Lift Motor	500 lb Max Thrust	500 lb Max Thrust	650 lb Max Thrust	800 lb Max Thrust	1000 lb Max Thrust	1000 lb Max Thrust
Product Weight	167 lbs	198 lbs	220 lbs	220 lbs	286 lbs	308 lbs
Max. User Weight	275 lbs	275 lbs	350 lbs	350 lbs	350 lbs	400 lbs
Floor Space	71" L x 31" W x 50" H	76" L x 34.5" W x 50" H	63.5" L x 32" W x 53" H	75" L x 35" W x 52" H	74" L x 36" W x 56" H	77" L x 36" W x 56" H
Folded Dimensions	39" L x 31" W x 60" H	39" L x 34" W x 64" H	32" L x 32" W x 59" H	39" L x 35" W x 64" H	N/A	N/A
<b>Home Use Warranty</b>						
Frame	LifeTime	LifeTime	LifeTime	LifeTime	LifeTime - Residential & Commercial	LifeTime - Residential & Commercial
Motor	LifeTime	LifeTime	LifeTime	LifeTime	5 Year Residential 5 Year Commercial	LifeTime Residential 5 Year Commercial
Parts	1 Year	3 Years	5 Years	5 Years	5 Year Residential 2 Year Commercial	5 Year Residential 2 Year Commercial
Labor	1 Year	1 Year	1 Year	1 Year	2 Year Residential 1 Year Commercial	2 Year Residential 1 Year Commercial
					Commercial Warranty cover up to 3 hours use per day	Commercial Warranty cover up to 6 hours use per day